

PRODUCT SPECIFICATIONS SHEET

CATEGORY | TRACK AND SPOT LUMINAIRES




KEY FEATURES

- LED COB up to 35W.
- **Luminaire efficacy:** Up to 110lm/W.
- **Heatsink:** Aluminium.
- **Mounting:** 4-Wire Track system.
- **Luminaire colour options:** White / Black / Custom colour on request.
- **Driver lifetime:** >100 000 hrs.
- **LED lifetime (L80B10):** >75 000 hrs.
- **Dimming options:** DALI, Bluetooth.
- Luminaire supplied with integrated in-track driver.


PHOTOMETRICS

LUMINAIRE DATA	NAME	DRAW POWER (W)	LED COLOUR (CCT)	COLOUR RENDERING INDEX (CRI)	LUMINOUS FLUX (LM)	LUMINAIRE EFFICACY (LM/W)	BEAM ANGLE
	ORAPA L	20	3000K, 3500K, 4000K, 5000K	92	1800 - 2200	90 - 110	12°/24°/33°/60°
	ORAPA L	30	3000K, 3500K, 4000K, 5000K	92	2700 - 3300	90 - 110	12°/24°/33°/60°
	ORAPA L	35	3000K, 3500K, 4000K, 5000K	92	3150 - 3850	90 - 110	12°/24°/33°/60°


PHOTOMETRICS




ORAPA L - 12°



ORAPA L - 24°



ORAPA L - 33°



ORAPA L - 60°

FIXTURE FEATURES AND WARRANTY






IP20

LED



5Year WARRANTY



GENERAL SPECIFICATIONS

GENERAL SPECIFICATIONS

DESCRIPTION	SPECIFICATION
LED chip type	Samsung / Vossloh Schwable
LED operating current	750 - 1050mA
LED working life (L80B 10)	>75 000hrs @ Ta=25 deg C
Driver type	Tridonic / Vossloh Schwable / TCI
Driver input voltage	110V - 230V
Driver power factor	>0.95λ
Driver nominal life	100 000hrs @ Ta=25 deg C
Driver dimming	Non - dim/ DALI / Bluetooth
Driver Total Harmonic Distortion (THD)	<20%
Driver surge protection (KV)	2KV
Driver compliance	EN 6 1347-2-13:2006
IP rating	IP20
SABS company certification	10089/15954
Operating temperature range	0°C to +35°C
Housing material	Aluminium / PMMA
Product warranty	5 Years
Product weight excluding packaging	+/- 0.52kg
Product weight including packaging	+/- 0.54kg

PRODUCT IMAGES



Front view



Rear view



Top view



Perspective view

General Disclaimer
Content is subject to change. Fluctuations in mains voltage and in LED forward voltage mean that lumen output and power draw may be subject to deviation(+5%) of rated value.

Liability Disclaimer
The contents of this document are for information purposes only and may be subject to change without prior notice. LED Lighting SA can not be held liable for any direct or indirect damages as a result of this information.
Copyright © LED Lighting 2019. All Rights Reserved.

CAPE TOWN
Head office
| 021 510 0028
| sales@ledlighting.co.za
| 1st Floor Hillwood House
25 Paarden Eiland Road
Paarden Eiland, 7405

JOHANNESBURG
Regional Branch
| 021 510 0028
| sales@ledlighting.co.za
| Office Unit 1 Pendoring Office Park,
299 Pendoring Rd, Blackheath,
Randburg, 2195

DURBAN
Regional Branch
021 510 0028
sales@ledlighting.co.za