

PRODUCT SPECIFICATIONS SHEET

CATEGORY | FOOD DISPLAY LUMINAIRES



KEY FEATURES


- **Power levels:** 15W/m
- **Luminaire efficacy:** Up to 106lm/W.
- **Heatsink:** Aluminium.
- **Mounting:** Surface. .
- Luminaire supplied with external driver.

PHOTOMETRICS

LUMINAIRE DATA	NAME	VOLTS (V)	DRAW POWER (W/m)	LENGTH (mm) (INCREMENTS OF 86mm)	LED COLOUR (CCT)	COLOUR RENDERING INDEX (CRI)
	SERENGETI	24	15	116mm - 2054mm	3000K	92

LUMINAIRE DATA	NAME	DRAW POWER (W/m)	WIDTH (mm)	HEIGHT (mm)	NOMINAL FLUX (LM/m)	LUMINAIRE EFFICACY (LM/W)	MAX CONNECTED LENGTH (m)
	SERENGETI	15	20.4	15.55	450 - 550	90 - 110	6

PHOTOMETRICS



SERENGETI

FIXTURE FEATURES AND WARRANTY



IP54



LED





GENERAL SPECIFICATIONS

GENERAL SPECIFICATIONS	DESCRIPTION	SPECIFICATION
	LED chip type	Samsung
	LED operating voltage	24V
	Driver type	External
	Driver dimming	Non - dim
	IP rating	IP54
	SABS company certification	10089/15954
	Operating temperature range	-20°C to +75°C
	Housing material	Aluminium/ Extruded silicone
	Product warranty	1 Year

PRODUCT IMAGES



Perspective view

General Disclaimer
Content is subject to change. Fluctuations in mains voltage and in LED forward voltage mean that lumen output and power draw may be subject to deviation(+/-5%) of rated value.

Liability Disclaimer
The contents of this document are for information purposes only and may be subject to change without prior notice. LED Lighting SA can not be held liable for any direct or indirect damages as a result of this information.

Copyright © LED Lighting 2019. All Rights Reserved.

 **CAPE TOWN**
Head office
| 021 510 0028
| sales@ledlighting.co.za
| 1st Floor Hillwood House
25 Paarden Eiland Road
Paarden Eiland, 7405

 **JOHANNESBURG**
Regional Branch
| 021 510 0028
| sales@ledlighting.co.za
| Office Unit 1 Pendoring Office Park,
299 Pendoring Rd, Blackheath,
Randburg, 2195

 **DURBAN**
Regional Branch
021 510 0028
sales@ledlighting.co.za