


PRODUCT SPECIFICATIONS SHEET

CATEGORY | SURFACE AND SUSPENDED




KEY FEATURES

- **Wattage:** Up to 87W.
- **Luminaire efficacy:** Up to 82lm/W.
- **Heatsink:** Chromadek
- **Mounting:** Surface or suspended.
- **Luminaire colour options:** White / Black / Custom colour on request.
- **LED lifetime (L80B10):** >75 000 hrs.
- **Dimming options:** DALI, Bluetooth, Touch DIM, 1-10, Triac, SPI
- **Custom sizes on request**
- Luminaire supplied with external driver.

PHOTOMETRICS

	NAME	DRAW POWER (W)	LED COLOUR (CCT)	COLOUR RENDERING INDEX (CRI)	LUMINOUS FLUX (LM)	LUMINAIRE EFFICACY (LM/W)	BEAM ANGLE
LUMINAIRE DATA	CHAAMBI 900	41 / 54	3000K, 3500K, 4000K, 5000K, RGBW, PIXEL RGBW	90	3362 - 4428	82	120°
	CHAAMBI 1200	54 / 72	3000K, 3500K, 4000K, 5000K, RGBW, PIXEL RGBW	90	4428 - 5904	82	120°
	CHAAMBI 1500	66 / 87	3000K, 3500K, 4000K, 5000K, RGBW, PIXEL RGBW	90	5412 - 7134	82	120°

PHOTOMETRICS



CHAAMBI 120°

FIXTURE FEATURES AND WARRANTY




IP20



5Year
WARRANTY


- X = 900mm; 1200mm; 1500mm
- Y= Width
- Depth: 60mm



GENERAL SPECIFICATIONS

GENERAL SPECIFICATIONS	
DESCRIPTION	SPECIFICATION
LED chip type	Samsung / Vossloh Schwable
LED operating voltage	24V
LED working life (L80B10)	>75 000hrs @ Ta = 25 deg C
Driver type	External
Driver dimming	Non - dim / DALI / Bluetooth / Touch DIM / 1-10 / Triac / SPI
IP rating	IP20
SABS company certification	10089/15954
Operating temperature range	0°C to +30°C
Housing material	Aluminium / Chromedek / Fabric

PRODUCT IMAGES



Perspective view

General Disclaimer
Content is subject to change. Fluctuations in mains voltage and in LED forward voltage mean that lumen output and power draw may be subject to deviation (+/-5%) of rated value.

Liability Disclaimer
The contents of this document are for information purposes only and may be subject to change without prior notice. LED Lighting SA can not be held liable for any direct or indirect damages as a result of this information.
Copyright © LED Lighting 2019. All Rights Reserved.

CAPE TOWN
Head office
| 021 510 0028
| sales@ledlighting.co.za
| 1st Floor Hillwood House
25 Paarden Eiland Road
Paarden Eiland, 7405

JOHANNESBURG
Regional Branch
| 021 510 0028
| sales@ledlighting.co.za
| Office Unit 1 Pendoring Office Park,
299 Pendoring Rd, Blackheath,
Randburg, 2195

DURBAN
Regional Branch
021 510 0028
sales@ledlighting.co.za