

PRODUCT SPECIFICATIONS SHEET

CATEGORY | RECESSED INLAY LUMINAIRES



KEY FEATURES


- **Luminaire efficacy:** Up to 84lm/W.
- **Mounting:** Replaces T-bar ceiling grid.
- **Luminaire colour options:** White / black / anodised .
- **Driver lifetime:** >100 000 hrs.
- **LED lifetime (L80B10):** >75 000 hrs.
- **Dimming options:** DALI, Bluetooth, Touch DIM
- Tuneable white available on request.
- Luminaire supplied with external driver.

PHOTOMETRICS

	NAME	DRAW POWER (W)	LED COLOUR (CCT)	COLOUR RENDERING INDEX (CRI)	LUMINOUS FLUX (LM)	LUMINAIRE EFFICACY (LM/W)	BEAM ANGLE
LUMINAIRE DATA	NKASA 600	20	3000K, 4000K, 5700K	80	1580 - 1680	79 - 84	BLOCK DIFFUSED
	NKASA 1200	40	3000K, 4000K, 5700K	80	3160 - 3360	79 - 84	BLOCK DIFFUSED
	NKASA 1200L	20	3000K, 4000K, 5700K	80	1580 - 1680	79 - 84	BLOCK DIFFUSED

NAME	LENGTH	WIDTH	HEIGHT
NKASA 600	576mm	25mm	70mm
NKASA 1200	1176mm	25mm	70mm
NKASA 1200L	1176mm	25mm	70mm

PHOTOMETRICS



NKASA – BLOCK DIFFUSED



FIXTURE FEATURES AND WARRANTY



IP20



5Year
WARRANTY



GENERAL SPECIFICATIONS

GENERAL SPECIFICATIONS

DESCRIPTION	SPECIFICATION
LED chip type	Samsung
LED operating current	350mA
LED working life (L80B10)	>75 000hrs @ Ta = 25 deg C
Driver type	Tridonic / Vossloh Schwable / TCI / Philips
Driver input voltage	110V - 230V
Driver power factor	>0.95A
Driver nominal life	100 000hrs @ Ta = 25 deg C
Driver dimming	Non - dim / DALI / Bluetooth / Touch DIM
Driver Total Harmonic Distortion (THD)	<20%
Driver surge protection (KV)	2KV
Driver compliance	EN 61347-2-13:2006
IP rating	IP20
SABS company certification	10089/15954
Operating temperature range	0°C to +40°C
Housing material	Aluminium / PMMA
Product warranty	5 Years
Product weight excluding packaging	+/- 1.33kg
Product weight including packaging	+/- 1.57kg

PRODUCT IMAGES



Front view

General Disclaimer
Content is subject to change. Fluctuations in mains voltage and in LED forward voltage mean that lumen output and power draw may be subject to deviation (+5%) of rated value.

Liability Disclaimer
The contents of this document are for information purposes only and may be subject to change without prior notice. LED Lighting SA can not be held liable for any direct or indirect damages as a result of this information.
Copyright © LED Lighting 2019. All Rights Reserved.

CAPE TOWN
Head office
| 021 510 0028
| sales@ledlighting.co.za
| 1st Floor Hillwood House
25 Paarden Eiland Road
Paarden Eiland, 7405

JOHANNESBURG
Regional Branch
| 021 510 0028
| sales@ledlighting.co.za
| Office Unit 1 Pendoring Office Park,
299 Pendoring Rd, Blackheath,
Randburg, 2195

DURBAN
Regional Branch
021 510 0028
sales@ledlighting.co.za