

PRODUCT SPECIFICATIONS SHEET

CATEGORY | STRIPLIGHT LUMINAIRES



KEY FEATURES


- **Power levels:** 5W/m, / 15W/m / 20W/m
- **Luminaire efficacy:** Up to 110lm/W.
- **Heatsink:** Aluminium.
- **Mounting:** Surface.
- **Luminaire colour options:** White / Black / Custom colour on request.
- **LED lifetime (L80B10):** >75 000 hrs.
- **Dimming options:** DALI, Bluetooth, Touch DIM, 1-10, Triac, PWM.
- Luminaire supplied with external driver.

PHOTOMETRICS

LUMINAIRE DATA	NAME	VOLTS (V)	DRAW POWER (W/m)	LENGTH (mm) (INCREMENTS OF 86mm)	LED COLOUR (CCT)	COLOUR RENDERING INDEX (CRI)
	AGULHAS	24	5	94mm - 2076mm	3000K, 3500K, 4000K,5700K	92
	AGULHAS	24	15	94mm - 2076mm	3000K, 3500K, 4000K,5700K	92
	AGULHAS	24	20	94mm - 2076mm	3000K, 3500K, 4000K,5700K	92

LUMINAIRE DATA	NAME	DRAW POWER (W/m)	WIDTH (mm)	HEIGHT (mm)	NOMINAL FLUX (LM/m)	LUMINAIRE EFFICACY (LM/W)	MAX CONNECTED LGTH (m)
	AGULHAS	5	20	18	450 - 550	90 - 110	6
	AGULHAS	15	20	18	1350 - 1650	90 - 110	6
	AGULHAS	20	20	18	1800 - 2200	90 - 110	4

PHOTOMETRICS



AGULHAS – DIFFUSED

FIXTURE FEATURES AND WARRANTY



IP20



5Year
WARRANTY



GENERAL SPECIFICATIONS

DESCRIPTION	SPECIFICATION
LED chip type	Samsung / Vossloh Schwable
LED operating voltage	24V
LED working life (L80B10)	>75 000hrs @ Ta = 25 deg C
Driver type	External
Driver dimming	Non - dim / DALI / Bluetooth / Touch DIM / 1-10 / Triac / PWM
IP rating	IP20
SABS company certification	10089/15954
Operating temperature range	0°C to + 40°C
Housing material	Aluminium / PMMA

Perspective view

General Disclaimer
Content is subject to change. Fluctuations in mains voltage and in LED forward voltage mean that lumen output and power draw may be subject to deviation (+/-5%) of rated value.

Liability Disclaimer
The contents of this document are for information purposes only and may be subject to change without prior notice. LED Lighting SA can not be held liable for any direct or indirect damages as a result of this information.

Copyright © LED Lighting 2019. All Rights Reserved.

Randburg, 2195