

PRODUCT SPECIFICATIONS SHEET

CATEGORY | STRIPLIGHT LUMINAIRES



KEY FEATURES


- **Power levels:** 5W/m / 10W/m / 15W/m / 20W/m
- **Luminaire efficacy:** Up to 110lm/W.
- **Heatsink:** Aluminium.
- **Mounting:** Surface.
- **Luminaire colour options:** White / Black / Custom colour on request.
- **LED lifetime (L80B10):** >75 000 hrs.
- **Dimming options:** DALI, Bluetooth, Touch DIM, 1-10, Triac, PWM.
- Luminaire supplied with external driver.

PHOTOMETRICS

LUMINAIRE DATA	NAME	VOLTS (V)	DRAW POWER (W)	LENGTH (mm) (INCREMENTS OF 86mm)	LED COLOUR (CCT)	COLOUR RENDERING INDEX (CRI)
	GAMBELA	24	5	94mm - 2158mm	3000K, 3500K, 4000K, 5700K	92
	GAMBELA	24	10	94mm - 2158mm	3000K, 3500K, 4000K, 5700K	92
	GAMBELA	24	15	94mm - 2158mm	3000K, 3500K, 4000K, 5700K	92
	GAMBELA	24	20	94mm - 2158mm	3000K, 3500K, 4000K, 5700K	92


LUMINAIRE DATA	NAME	DRAW POWER (W)	WIDTH (mm)	HEIGHT (mm)	NOMINAL FLUX (LM/m)	LUMINAIRE EFFICACY (LM/W)	MAX CONNECTED LGTH (m)
	GAMBELA	5	17	20	450 - 550	90 - 110	6
	GAMBELA	10	17	20	900 - 1100	90 - 110	6
	GAMBELA	15	17	20	1350 - 1650	90 - 110	6
	GAMBELA	20	17	20	1800 - 2200	90 - 110	4

PHOTOMETRICS





PRODUCT DRAWING DIMENSIONS



GENERAL SPECIFICATIONS

GENERAL SPECIFICATIONS	DESCRIPTION	SPECIFICATION
	LED chip type	Samsung / Vossloh Schwable
	LED operating voltage	24V
	LED working life (L80B10)	>75 000hrs @ Ta = 25 deg C
	Driver type	External
	Driver dimming	Non - dim / DALI / Bluetooth / Touch DIM / 1-10 / Triac / PWM
	IP rating	IP20
	SABS company certification	10089/15954
	Operating temperature range	0°C to +40°C
	Housing material	Aluminium / PMMA

PRODUCT IMAGES



Perspective view

General Disclaimer
 Content is subject to change. Fluctuations in mains voltage and in LED forward voltage mean that lumen output and power draw may be subject to deviation (+/-5%) of rated value.

Liability Disclaimer
 The contents of this document are for information purposes only and may be subject to change without prior notice. LED Lighting SA can not be held liable for any direct or indirect damages as a result of this information.

Copyright © LED Lighting 2019. All Rights Reserved.

CAPE TOWN
 Head office
 | 021 510 0028
 | sales@ledlighting.co.za
 | 1st Floor Hillwood House
 25 Paarden Eiland Road
 Paarden Eiland, 7405

JOHANNESBURG
 Regional Branch
 | 021 510 0028
 | sales@ledlighting.co.za
 | Office Unit 1 Pendoring Office Park,
 299 Pendoring Rd, Blackheath,
 Randburg, 2195

DURBAN
 Regional Branch
 021 510 0028
 sales@ledlighting.co.za