

PRODUCT SPECIFICATIONS SHEET

CATEGORY | SURFACE AND SUSPENDED




KEY FEATURES

- **Wattage:** Up to 88W.
- **Luminaire efficacy:** Up to 82lm/W.
- **Heatsink:** Chromadek
- **Mounting:** Surface or suspended.
- **Luminaire colour options:** White / Black / Custom colour on request.
- **LED lifetime (L80B10):** >75 000 hrs.
- **Dimming options:** DALI, Bluetooth, Touch DIM, 1-10, Triac, SPI
- **Custom sizes on request**
- Luminaire supplied with external driver.

PHOTOMETRICS

LUMINAIRE DATA	NAME	DRAW POWER (W)	LED COLOUR (CCT)	COLOUR RENDERING INDEX (CRI)	LUMINOUS FLUX (LM)	LUMINAIRE EFFICACY (LMW)	BEAM ANGLE
	MANDA 900	42 / 55	3000K, 3500K, 4000K, 5000K, RGBW, PIXEL RGBW	90	3444 - 4510	82	120°
	MANDA 1200	55 / 73	3000K, 3500K, 4000K, 5000K, RGBW, PIXEL RGBW	90	4510 - 5986	82	120°
	MANDA 1500	66 / 88	3000K, 3500K, 4000K, 5000K, RGBW, PIXEL RGBW	90	5412 - 7216	82	120°

PHOTOMETRICS



MANDA 120°

FIXTURE FEATURES AND WARRANTY




IP20



5Year
WARRANTY

- X = 900mm; 1200mm; 1500mm
- Width=50mm
- Depth: 60mm



GENERAL SPECIFICATIONS

GENERAL SPECIFICATIONS	DESCRIPTION	SPECIFICATION
	LED chip type	Samsung / Vossloh Schwable
	LED operating voltage	24V
	LED working life (L80B10)	>75 000hrs @ Ta = 25 deg C
	Driver type	External
	Driver dimming	Non - dim / DALI / Bluetooth / Touch DIM / 1-10 / Triac / SPI
	IP rating	IP20
	SABS company certification	10089/15954
	Operating temperature range	0°C to +30°C
	Housing material	Aluminium / Chromedek / Fabric

PRODUCT IMAGES



Perspective view

General Disclaimer

Content is subject to change. Fluctuations in mains voltage and in LED forward voltage mean that lumen output and power draw may be subject to deviation (+/-5%) of rated value.

Liability Disclaimer

The contents of this document are for information purposes only and may be subject to change without prior notice. LED Lighting SA can not be held liable for any direct or indirect damages as a result of this information.

Copyright © LED Lighting 2019. All Rights Reserved.

CAPE TOWN Head office

| 021 510 0028
| sales@ledlighting.co.za
| 1st Floor Hillwood House
25 Paarden Eiland Road
Paarden Eiland, 7405

JOHANNESBURG Regional Branch

| 021 510 0028
| sales@ledlighting.co.za
| Office Unit 1 Pendoring Office Park,
299 Pendoring Rd, Blackheath,
Randburg, 2195

DURBAN Regional Branch

021 510 0028
sales@ledlighting.co.za