

PRODUCT SPECIFICATIONS SHEET

CATEGORY | RECESSED INLAY LUMINAIRES



KEY FEATURES


- **Luminaire efficacy:** Up to 87lm/W.
- **Mounting:** Replaces T-bar ceiling grid.
- **Luminaire colour options:** White / black / anodised .
- **Driver lifetime:** >100 000 hrs.
- **LED lifetime (L80B10):** >75 000 hrs.
- **Dimming options:** DALI, Bluetooth, Touch DIM
- Tunable white available on request.
- Luminaire supplied with external driver.

PHOTOMETRICS

LUMINAIRE DATA	NAME	DRAW POWER (W)	LED COLOUR (CCT)	COLOUR RENDERING INDEX (CRI)	LUMINOUS FLUX (LM)	LUMINAIRE EFFICACY (LM/W)	BEAM ANGLE
	NSUMBU 600	20	3000K, 4000K, 5700K	80	1660 - 1740	83 - 87	PRISMATIC
	NSUMBU 1200	40	3000K, 4000K, 5700K	80	3320 - 3480	83 - 87	PRISMATIC
	NSUMBU 1200L	20	3000K, 4000K, 5700K	80	1660 - 1740	83 - 87	PRISMATIC

NAME	LENGTH	WIDTH	HEIGHT
NSUMBU 600	576mm	24mm	51mm
NSUMBU 1200	1176mm	24mm	51mm
NSUMBU 1200L	1176mm	24mm	51mm

PHOTOMETRICS



NSUMBU – PRISMATIC



FIXTURE FEATURES AND WARRANTY



IP20



5Year
WARRANTY



GENERAL SPECIFICATIONS

GENERAL SPECIFICATIONS	DESCRIPTION	SPECIFICATION
	LED chip type	Samsung
	LED operating current	350mA
	LED working life (L80B10)	>75 000hrs @ Ta = 25 deg C
	Driver type	Tridonic / Vossloh Schwabe / TCI / Philips
	Driver input voltage	110V - 230V
	Driver power factor	>0.95A
	Driver nominal life	100 000hrs @ Ta = 25 deg C
	Driver dimming	Non - dim / DALI / Bluetooth / Touch DIM
	Driver Total Harmonic Distortion (THD)	<20%
	Driver surge protection (KV)	2KV
	Driver compliance	EN 61347-2-13:2006
	IP rating	IP20
	SABS company certification	10089/15954
	Operating temperature range	0°C to +40°C
	Housing material	Aluminium / PMMA
	Product warranty	5 Years
	Product weight excluding packaging	+/- 133kg
	Product weight including packaging	+/- 157kg

PRODUCT IMAGES



Front view

General Disclaimer

Content is subject to change. Fluctuations in mains voltage and in LED forward voltage mean that lumen output and power draw may be subject to deviation (+/-5%) of rated value.

Liability Disclaimer

The contents of this document are for information purposes only and may be subject to change without prior notice. LED Lighting SA can not be held liable for any direct or indirect damages as a result of this information.

Copyright © LED Lighting 2019. All Rights Reserved.

CAPE TOWN Head office

| 021 510 0028
| sales@ledlighting.co.za
| 1st Floor Hillwood House
25 Paarden Eiland Road
Paarden Eiland, 7405

JOHANNESBURG Regional Branch

| 021 510 0028
| sales@ledlighting.co.za
| Office Unit 1 Pendoring Office Park,
299 Pendoring Rd, Blackheath,
Randburg, 2195

DURBAN Regional Branch

021 510 0028
| sales@ledlighting.co.za