

## PRODUCT SPECIFICATIONS SHEET

## CATEGORY | DOWNLIGHT LUMINAIRES




### KEY FEATURES

- **LED COB up to 30W.**
- **Luminaire efficacy:** Up to 110lm/W.
- **Heatsink:** Aluminium
- **Mounting:** Ceiling mounted recessed .
- **Luminaire colour options:** White / Black / Custom colour on request.
- **Driver lifetime:** >100 000 hrs.
- **LED lifetime (L80B10):** >75 000 hrs.
- **Dimming options:** DALI, Bluetooth, Touch DIM
- Luminaire supplied with external driver.


## PHOTOMETRICS

| LUMINAIRE DATA | NAME             | DRAW POWER (W) | LED COLOUR (CCT)           | COLOUR RENDERING INDEX (CRI) | LUMINOUS FLUX (LM) | LUMINAIRE EFFICACY (LM/W) | BEAM ANGLE      |
|----------------|------------------|----------------|----------------------------|------------------------------|--------------------|---------------------------|-----------------|
|                | ETOSHA 315X160 R | 16             | 3000K, 3500K, 4000K ,5000K | 92                           | 1440 - 1760        | 90 - 110                  | 20°/30°/38°/60° |
|                | ETOSHA 315X160 R | 30             | 3000K, 3500K, 4000K ,5000K | 92                           | 2700 - 3300        | 90 - 110                  | 20°/30°/38°/60° |


## PHOTOMETRICS




ETOSHA 315X160 R 20°



ETOSHA 315X160 L 30°



ETOSHA 315X160 L 38°



ETOSHA 315X160 L 60°

## FIXTURE FEATURES AND WARRANTY




IP20





**5Year**  
WARRANTY

Cut out size:



- (16W & 30W) = 130mm
- Dimensions: 330x175mm
- Cut out: 315x160mm



## GENERAL SPECIFICATIONS

| GENERAL SPECIFICATIONS | DESCRIPTION                            | SPECIFICATION                            |
|------------------------|----------------------------------------|------------------------------------------|
|                        | LED chip type                          | Samsung / Vossloh Schwable               |
|                        | LED operating current                  | 450 - 750mA                              |
|                        | LED working life (L80B 10)             | >75 000hrs @ Ta = 25 deg C               |
|                        | Driver type                            | Tridonic / Vossloh Schwable / TCI        |
|                        | Driver input voltage                   | 110V - 230V                              |
|                        | Driver power factor                    | >0.95λ                                   |
|                        | Driver nominal life                    | 100 000hrs @ Ta = 25 deg C               |
|                        | Driver dimming                         | Non - dim / DALI / Bluetooth / Touch DIM |
|                        | Driver Total Harmonic Distortion (THD) | <20%                                     |
|                        | Driver surge protection (KV)           | 2KV                                      |
|                        | Driver compliance                      | EN 61347-2-13:2006                       |
|                        | IP rating                              | IP20                                     |
|                        | SABS company certification             | 10089/15954                              |
|                        | Operating temperature range            | 0°C to +30°C                             |
|                        | Housing material                       | Aluminium / Plastic                      |
|                        | Product warranty                       | 5 Years                                  |
|                        | Product weight excluding packaging     | +/- 2.88kg                               |
|                        | Product weight including packaging     | +/- 3.12kg                               |

## PRODUCT IMAGES



Front view



Rear view



Top view



Perspective view

### General Disclaimer

Content is subject to change. Fluctuations in mains voltage and in LED forward voltage mean that lumen output and power draw may be subject to deviation (+/-5%) of rated value.

### Liability Disclaimer

The contents of this document are for information purposes only and may be subject to change without prior notice. LED Lighting SA can not be held liable for any direct or indirect damages as a result of this information.

Copyright © LED Lighting 2019. All Rights Reserved.

### CAPE TOWN Head office

| 021 510 0028  
| [sales@ledlighting.co.za](mailto:sales@ledlighting.co.za)  
| 1st Floor Hillwood House  
25 Paarden Eiland Road  
Paarden Eiland, 7405

### JOHANNESBURG Regional Branch

| 021 510 0028  
| [sales@ledlighting.co.za](mailto:sales@ledlighting.co.za)  
| Office Unit 1 Pendoring Office Park,  
299 Pendoring Rd, Blackheath,  
Randburg, 2195

### DURBAN Regional Branch

021 510 0028  
[sales@ledlighting.co.za](mailto:sales@ledlighting.co.za)